

FLOS

 F004H30AU71 Anodized Black

Landlord Soft PWM Dimmable Anodized Black

Designed by Piero Lissoni, 2018



20° adjustable head for installation on ground poles. Poles to be ordered as separated accessories. 24V remote power supply to be ordered separately. Each head comes with a 2000mm lenght outgoing cable and a wiring kit.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8054793203232
Mounting	Ground
Environments	Outdoor wet location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	5
System flux (lm)	252

Physical

Color	Anodized Black
Orientation	Adjustable
Rotation (°)	359
Transversal tilting (°)	20
Net weight (lb)	0.6
Gross weight (lb)	0.66
Package height (in)	4.13
Package width (in)	6.42
Package length (in)	6.42
Package volume (in)	170.26
IP internal	65



Download

[Family spec sheet](#)  ZIP

[Mounting instructions](#)  ZIP

Photometric Files


[LDT / IES](#)  ZIP

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Photometric

Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	51
Beam angle C90-270 (°)	51
Extreme cut off	No

Electrical

Insulation class	III
Main voltage (Vac)	24
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable DALI PWM, Dimmable 1-10 PWM
Dimming interface	Remote Dimmable (Dimmer Not Included)
Emergency type	No

Notes

Carefully install and maintain the fixtures to avoid damaging the coating.
For LED fixtures, most problems are tied to electrical issues related to the insulation, which may cause destructive electrical discharges.
These are frequently caused by:

- power surges from the power network where fixture is connected.
- electrostatic discharge (ESD) from the environment.

We recommend installing a power-surge protection device on the fixture to reduce the intensity of these effects and prevent irreversible damages. The specific device should be chosen based on the electrical characteristics.

Accessories & Power Supply



REQUIRED
Accessory

F004Z0F0071
Pole with base H 900 mm
Anodized Black



REQUIRED
Accessory

F004Z0E0071
Pole with base H 600 mm
Anodized Black



REQUIRED
Accessory

F004Z0D0071
Pole with base H 300 mm
Anodized Black



OPTIONAL
Accessory

F004Z070000
Tree strap



OPTIONAL
Accessory

F004Z060000
Earth stick