

 FA53610356 Matte Stainless Steel

## Leila 1 Stainless Steel Frame

Designed by FLOS Outdoor, 2013

LED source included. Electrical power supply 220-240V ON/OFF: remote kit with a 400mm cable section with watertight threaded M12 connector on the luminaire and a 250mm cable section for connection on the mains. This needs to be housed in the junction box for masonry ceilings (it needs to be ordered separately) or set next to the luminaire in case of plasterboard false ceilings. Dimmable version available upon request.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

|                        |                      |
|------------------------|----------------------|
| EAN                    | 8054793677507        |
| Mounting               | Ceiling recessed     |
| Environments           | Outdoor wet location |
| Light source type      | LED                  |
| Light sources included | Yes                  |
| LED type               | LED array            |
| Number of lamps        | 1                    |
| System power (W)       | 12                   |
| Source flux (lm)       | 1179                 |
| Lumen Output (lm)      | 859                  |

### Physical

|                     |                       |
|---------------------|-----------------------|
| Colour              | Matte Stainless Steel |
| Orientation         | Fixed                 |
| Net weight (kg)     | 0.51                  |
| Package height (mm) | 150                   |
| Package width (mm)  | 135                   |
| Package length (mm) | 180                   |
| IP internal         | 66                    |
| IP external         | 66                    |

 Drawing Thumbnail

[Download](#)

[Photometric Files](#)


[Technical Drawings](#)

### Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Non-replaceable light source



Replaceable control gear by an end-user



## Photometric

|                        |           |
|------------------------|-----------|
| Light distribution     | Symmetric |
| CCT (K)                | 2700      |
| CRI>                   | 80        |
| Beam angle C0-180 (°)  | 19        |
| Beam angle C90-270 (°) | 19        |
| Extreme cut off        | No        |

## Electrical

|                    |                 |
|--------------------|-----------------|
| Insulation class   | II              |
| Frequency (Hz)     | 50/60           |
| Main voltage (Vac) | 220-240         |
| Power supply       | Remote included |
| Dimmable           | No              |
| Power supply type  | Non Dimmable    |
| Dimming interface  | Not Dimmable    |
| Emergency          | No              |

## Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance'  
Dimmable version on request

---

## Accessories & Power Supply



REQUIRED  
Accessory

FA196

Box for Ceiling Recessed  
Installation Leila 1



OPTIONAL  
Accessory

F990C00A000


2 way terminal block 4 poles IP68  
H2O stop. (ø5,5÷12mm cable)



OPTIONAL  
Accessory

F990C010000

3/4 way terminal block 4 poles  
IP68 H2O stop. (ø5,5÷12mm  
cable)



OPTIONAL  
Accessory

F990E00A000

S.P.D. (SURGE PROTECTION  
DEVICE)