


FLOS


FA53601201 White

Leila 1 White Painted Frame

Designed by FLOS Outdoor, 2013



LED source included. Electrical power supply 220-240V ON/OFF: remote kit with a 400mm cable section with watertight threaded M12 connector on the luminaire and a 250mm cable section for connection on the mains. This needs to be housed in the junction box for masonry ceilings (it needs to be ordered separately) or set next to the luminaire in case of plasterboard false ceilings. Dimmable version available upon request.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8054793674407
Mounting	Ceiling recessed
Light source type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
System power (W)	12
Source flux (lm)	1229
Lumen Output (lm)	980

Physical

Colour	White
Orientation	Fixed
Net weight (kg)	0.51
Package height (mm)	150
Package width (mm)	135
Package length (mm)	180
IP internal	66
IP external	66

Download

[Mounting instructions](#) ZIP

Photometric Files

[LDT / IES](#) ZIP


Technical Drawings

[2D](#) ZIP

[3D](#) ZIP



Schematic light drawing



h(m)	E(lx)	D(m)
1	1779	0.79
2	445	1.57
3	198	2.36
4	111	3.14
5	71	3.93

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	43
Beam angle C90-270 (°)	43
Extreme cut off	No

Electrical


Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Remote included
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Non-replaceable light source



Replaceable control gear by an end-user

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance!
Dimmable version on request

Accessories & Power Supply



REQUIRED
Accessory

FA196

Box for Ceiling Recessed
Installation Leila 1



OPTIONAL
Accessory

F990C00A000

2 way terminal block 4 poles IP68
H2O stop. (ø5,5÷12mm cable)



OPTIONAL
Accessory

F990C010000

3/4 way terminal block 4 poles
IP68 H2O stop. (ø5,5÷12mm
cable)



OPTIONAL
Accessory

F990E00A000

S.P.D. (SURGE PROTECTION
DEVICE)