

Light Bell No Dimmable

Designed by Piero Lissoni, 2016



LED - LED array - 55W - 3000K - CRI> 90 - Beam° 78

Suspended luminaire for mounting on the ceiling with LED light source. (4 metres maximum distance to ceiling). Power supply source integrated into luminaire housing. Reflector not included; supplied separately.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                  |                     |
|------------------|---------------------|
| Mounting         | Suspension          |
| Environments     | Indoor dry location |
| LED type         | LED array           |
| Lamp category    | LED                 |
| Number of lamps  | 1                   |
| Power (W)        | 55                  |
| Source flux (lm) | 6714                |

### Physical

|                  |       |
|------------------|-------|
| Colour           | Black |
| Trim             | No    |
| Orientation      | Fixed |
| Cord length (mm) | 4000  |
| Net weight (kg)  | 3.81  |
| IP internal      | 20    |



### Download

Mounting instructions [ZIP](#)

### Photometric Files

LDT / IES [ZIP](#)

### Technical Drawings


2D [ZIP](#)

3D [ZIP](#)

[Bim](#) [ZIP](#)



Schematic light drawing



Photometric

|                          |                  |
|--------------------------|------------------|
| Lighting type            | Direct           |
| Light distribution       | Symmetric        |
| CCT (K)                  | 3000             |
| CRI>                     | 90               |
| LED Life / Failure Ratio | L90B10 > 50.000h |
| Beam angle C0-180 (°)    | 78               |
| Beam angle C90-270 (°)   | 78               |
| Extreme cut off          | No               |

Electrical

|                    |              |
|--------------------|--------------|
| Insulation class   | I            |
| Frequency (Hz)     | 50/60        |
| Main voltage (Vac) | 220-240      |
| Power supply       | Integrated   |
| Dimmable           | No           |
| Power supply type  | Non Dimmable |
| Emergency          | No           |

Notes

Pin-block type dissipater. Please ask us for a higher IP. Includes a 4-meter suspension cable.

Accessories & Power Supply



OPTIONAL  
Accessory

07.9630.70

Light Bell Reflector



OPTIONAL  
Accessory

07.9630.76

Light Bell Reflector



OPTIONAL  
Accessory

07.9630.AN

Light Bell Reflector



OPTIONAL  
Accessory

07.9630.AP


Light Bell Reflector



OPTIONAL  
Accessory

07.9630.CE

Light Bell Reflector



OPTIONAL  
Accessory

08.8775.40

Rosette. IP20



OPTIONAL  
Accessory

F0556020


Light Bell Canopy Power supply  
for standard and dimmable  
versions



OPTIONAL  
Accessory

F0557020

Rosette for indoors. IP20.  
Dimmable Push/Dali



## OPTIONAL Accessory

08.8775.14

Rosette. IP20