


Light Shadow Adjustable No Trim 12 Spots Optic Flood

Designed by FLOS Architectural, 2022

LED - Power LED - 32.4W - 3035lm - 2700K - CRI> 90 - Beam° 29

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	32.4
System power (W)	32.4
Source flux (lm)	3576
Lumen Output (lm)	3035
Efficacy (lm/W)	93

Physical

Colour	Black/Steel
Trim	No
Orientation	Adjustable
Longitudinal tilting (°)	30
Recessed depth (mm)	75
Length (mm)	429
Net weight (kg)	0.66
Package height (mm)	16
Package width (mm)	14
Package length (mm)	21
IP internal	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)


Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional

 Replaceable control gear by a professional



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B20 >50.000h (Tc=85°C)
Beam angle C0-180 (°)	29
Beam angle C90-270 (°)	28
Extreme cut off	No
UGRL	<10

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
LED current (mA)	900
Power supply	Remote included
Dimmable	No
Power supply type	Non Dimmable

Notes

Accessories & Power Supply



REQUIRED
Frame

ACCESSORYTYPE2

08.0518.00

Pre-installation No Trim Frame
12L Fix Adjustable



OPTIONAL
Accessory

ACCESSORYTYPE2

08.0059.90

Accessory for mounting of No
Trim Adjustable continuous line.