

03.9406.14CUQ Black/Black

Light Shadow Adjustable No Trim 2 Spots Optic Flood - Non IC

Designed by FLOS Architectural, 2022

LED - Power LED - 7W - 493lm - 2700K - CRI> 90 - Beam° 30

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	7
System power (W)	7
Source flux (lm)	596
System flux (lm)	493
Efficacy (lm/W)	70

Physical

Color	Black/Black
Trim	No
Orientation	Adjustable
Longitudinal tilting (°)	30
IP internal	20



Download

- Family spec sheet [ZIP](#)
- Mounting instructions [PDF](#)

Photometric Files


- LDT / IES [ZIP](#)

Technical Drawings

- 2D [ZIP](#)
- 3D [ZIP](#)



Schematic light drawing



Ecodesign and Energy
Labelling

Replaceable (LED only)
light source by a
professional

Replaceable control
gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B20 >50.000h (Tc=85°C)
Beam angle C0-180 (°)	30
Beam angle C90-270 (°)	28
Extreme cut off	No
UGRL	<10

Electrical

Forward voltage (V)	7
LED current (mA)	900
Driver	Integral - Splice Box
Dimmable	Yes
Dimming type	Dimmable 0-10V, Dimmable ELV
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes

It requires a pre-installation frame, to be ordered separately.

Accessories & Power Supply



REQUIRED
Accessory

ACCESSORYTYPE2

08.0515.00.90
Pre-installation No Trim Frame 2L
Adjustable



REQUIRED
Power supply

SP20W900MA-120-C01
Splice Box 9"x2.22"x1.25", 900mA
, 20W, 0-10V Dimmable, Thermal
120V



REQUIRED
Power supply

SP20W900MA-277-C01
Splice Box 9"x2.22"x1.25", 900mA
, 20W, 0-10V Dimmable, Thermal
277V



REQUIRED
Power supply


SP20W900MA-ELV-C01
Splice Box 9"x2.22"x1.25", 900mA
, 20W, ELV Dimmable, Thermal
120V



OPTIONAL
Accessory

ACCESSORYTYPE2

08.0059.90
Accessory for mounting of No
Trim Adjustable continuous line.



OPTIONAL
Housing and Hanger Bar

TRAY-0031
Registration Tray - non electrical,
place holder for non IC new
construction for Light Shadow
Fixed 2 Light Trim