




05.1476.40C90 White/Steel

Light Shadow Adjustable No Trim 2 Spots Optic Wide Flood - Airtight IC Rated

Designed by FLOS Architectural, 2022




LED - Power LED - 7.2W - 532lm - 3000K - CRI> 90 - Beam° 45

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	7.2
System power (W)	7
Source flux (lm)	636
System flux (lm)	532
Efficacy (lm/W)	76

Physical

Color	White/Steel
Trim	No
Orientation	Adjustable
Longitudinal tilting (°)	30
Net weight (lb)	0.56
Gross weight (lb)	0.67
Package volume (in)	244.08
IP internal	20

Download

- [Family spec sheet](#) ZIP
- [Mounting instructions](#) PDF

Photometric Files


- [LDT / IES](#) ZIP

Technical Drawings

- [2D](#) ZIP
- [3D](#) ZIP



Schematic light drawing



Ecodesign and Energy
Labelling



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B20 >50.000h (Tc=85°C)
Beam angle C0-180 (°)	45
Beam angle C90-270 (°)	45
Extreme cut off	No
UGRL	<10

Electrical

Forward voltage (V)	8
LED current (mA)	900
Driver	Remote
Dimmable	Yes
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes

It requires a pre-installation frame, to be ordered separately.

Accessories & Power Supply



REQUIRED
Accessory

ACCESSORYTYPE2

08.0515.00.90
Pre-installation No Trim Frame 2L
Adjustable



REQUIRED
Housing and Hanger Bar

08.1201.00.UL
Bar Hanger Set , Male-Female (set
of 2)



REQUIRED
Housing and Hanger Bar

08.7064.00A90
Light Shadow 2 Spots Adjustable
Trim-Trimsless, Airtight Housing
for New construction, Integral 0-
10V dimmable driver. CCEA
Chicago Plenum