



05.1676.40CUQ White/Steel

Light Shadow Adjustable No Trim 8 Spots Optic Wide Flood - Non IC

Designed by FLOS Architectural, 2022




LED - Power LED - 21.6W - 2127lm - 3000K - CRI> 90 - Beam° 45

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	21.6
System power (W)	21.6
Source flux (lm)	2544
System flux (lm)	2127
Efficacy (lm/W)	98

Physical

Color	White/Steel
Trim	No
Orientation	Adjustable
Longitudinal tilting (°)	30
Net weight (lb)	1.11
Gross weight (lb)	1.36
Package volume (in)	366.12
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	---------------------

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Ecodesign and Energy
Labelling

Replaceable (LED only)
light source by a
professional

Replaceable control
gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B20 >50.000h (Tc=85°C)
Beam angle C0-180 (°)	45
Beam angle C90-270 (°)	45
Extreme cut off	No
UGRL	<10

Electrical

Forward voltage (V)	25.8
LED current (mA)	900
Driver	Integral - Splice Box
Dimmable	Yes
Dimming type	Dimmable 0-10V, Dimmable ELV
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes

It requires a pre-installation frame, to be ordered separately.

Accessories & Power Supply



REQUIRED
Accessory

ACCESSORYTYPE2

08.0517.00.90
Pre-installation No Trim Frame 8L
Fix Adjustable



REQUIRED
Power supply

SP25W900MA-120-A01
Splice Box 9"x3.59"x1.25", 900mA
, 25W, 0-10V Dimmable, Thermal
120V



REQUIRED
Power supply

SP25W900MA-277-A01
Splice Box 9"x3.59"x1.25", 900mA
, 25W, 0-10V Dimmable, Thermal
277V



REQUIRED
Power supply

SP30W900MA-ELV-U01
Splice Box 7"x3.59"x1.25", 900mA ,
30W, ELV Dimmable, Thermal
120V



OPTIONAL
Accessory

ACCESSORYTYPE2

08.0059.90
Accessory for mounting of No
Trim Adjustable continuous line.