

Light Shadow Adjustable No Trim Mains Dimming
Version 8 Spots Optic Spot

Designed by FLOS Architectural, 2022



LED - 1989lm - 3000K - CRI> 90 - Beam° 11

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
Lamp category	LED
Number of lamps	1
System power (W)	18
Source flux (lm)	2272
Lumen Output (lm)	1989
Efficacy (lm/W)	110

Physical

Colour	Black/Steel
Trim	No
Orientation	Adjustable
Longitudinal tilting (°)	30
Recessed depth (mm)	75
Length (mm)	429
Net weight (kg)	0.66
IP internal	20

Download

Mounting instructions  PDF

Photometric Files

LDT / IES  ZIP


Technical Drawings

2D  ZIP

3D  ZIP


Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional

 Replaceable control gear by a professional



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B20 >50.000h (Tc=85°C)
Beam angle C0-180 (°)	11
Beam angle C90-270 (°)	12
Extreme cut off	No
UGRL	<10

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Remote included
Dimmable	Yes
Power supply type	Mains Cut Dimming

Notes

Accessories & Power Supply



REQUIRED
Frame

ACCESSORYTYPE2

08.0517.00

Pre-installation No Trim Frame 8L
Fix Adjustable



OPTIONAL
Accessory

ACCESSORYTYPE2

08.0059.90

Accessory for mounting of No
Trim Adjustable continuous line.