



05.1526.14C90 Black/Steel

## Light Shadow Adjustable Trim 4 Spots Optic Flood - Airtight IC Rated

Designed by FLOS Architectural



LED - Power LED - 10.8W - 1079lm - 3000K - CRI> 90 - Beam° 29

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 10.8                |
| System power (W)       | 10.8                |
| Source flux (lm)       | 1272                |
| System flux (lm)       | 1079                |
| Efficacy (lm/W)        | 99                  |

### Physical

|                          |             |
|--------------------------|-------------|
| Color                    | Black/Steel |
| Trim                     | Yes         |
| Orientation              | Adjustable  |
| Longitudinal tilting (°) | 30          |
| Net weight (lb)          | 0.75        |
| Gross weight (lb)        | 1.02        |
| Package volume (in)      | 244.08      |
| IP internal              | 20          |



### Download

- Family spec sheet [ZIP](#)
- Mounting instructions [PDF](#)

### Photometric Files


- LDT / IES [ZIP](#)

### Technical Drawings

- 2D [ZIP](#)
- 3D [ZIP](#)



Schematic light drawing



### Ecodesign and Energy Labelling



Replaceable (LED only)  
light source by a  
professional



Replaceable control  
gear by a professional

Photometric

|                          |                             |
|--------------------------|-----------------------------|
| Lighting type            | Direct                      |
| Light distribution       | Symmetric                   |
| CCT (K)                  | 3000                        |
| CRI>                     | 90                          |
| LED Life / Failure Ratio | L80B50>50.000h<br>(Tc=85°C) |
| Beam angle C0-180 (°)    | 29                          |
| Beam angle C90-270 (°)   | 28                          |
| Extreme cut off          | No                          |
| UGRL                     | <10                         |

Electrical

|                     |                                          |
|---------------------|------------------------------------------|
| Forward voltage (V) | 12.9                                     |
| LED current (mA)    | 900                                      |
| Driver              | Remote                                   |
| Dimmable            | Yes                                      |
| Dimming interface   | Remote Dimmable<br>(Dimmer Not Included) |

Notes

Pre-Installation frame not required.

Accessories & Power Supply



REQUIRED  
Housing and Hanger Bar

08.1201.00.UL

Bar Hanger Set , Male-Female (set of 2)



REQUIRED  
Housing and Hanger Bar

08.7066.00A90

Light Shadow 4 Lights Adjustable Trim-Trimsless, Airtight Housing for New construction, Integral 0-10V dimmable driver. CCEA Chicago Plenum