

FLOS

05.1537.14C90 Black/Bronze

Light Shadow Adjustable Trim 4 Spots Optic Wide Flood - Airtight IC Rated

Designed by FLOS Architectural

LED - Power LED - 10.8W - 1056lm - 3000K - CRI> 90 - Beam° 46

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	10.8
System power (W)	10.8
Source flux (lm)	1272
System flux (lm)	1056
Efficacy (lm/W)	97

Physical

Color	Black/Bronze
Trim	Yes
Orientation	Adjustable
Longitudinal tilting (°)	30
Net weight (lb)	0.75
Gross weight (lb)	1.02
Package volume (in)	244.08
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Ecodesign and Energy
Labelling



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C)
Beam angle C0-180 (°)	46
Beam angle C90-270 (°)	46
Extreme cut off	No
UGRL	<10

Electrical

Forward voltage (V)	12.9
LED current (mA)	900
Driver	Remote
Dimmable	Yes
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes

Pre-Installation frame not required.

Accessories & Power Supply



REQUIRED
Housing and Hanger Bar

08.1201.00.UL

Bar Hanger Set , Male-Female (set of 2)



REQUIRED
Housing and Hanger Bar

08.7066.00A90

Light Shadow 4 Lights Adjustable Trim-Trimsless, Airtight Housing for New construction, Integral 0-10V dimmable driver. CCEA Chicago Plenum