

Light Shadow Adjustable Trim Mains Dimming  
Version 8 Spots Optic Wide Flood

Designed by FLOS Architectural



LED - 1692lm - 2700K - CRI> 90 - Beam° 45

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| System power (W)       | 18                  |
| Source flux (lm)       | 2024                |
| Lumen Output (lm)      | 1692                |
| Efficacy (lm/W)        | 94                  |

### Physical

|                          |             |
|--------------------------|-------------|
| Colour                   | Black/Steel |
| Trim                     | Yes         |
| Orientation              | Adjustable  |
| Longitudinal tilting (°) | 30          |
| Recessed depth (mm)      | 75          |
| Length (mm)              | 429         |
| Net weight (kg)          | 0.66        |
| IP internal              | 20          |

### Download

Mounting instructions  PDF

### Photometric Files

LDT / IES  ZIP


### Technical Drawings

2D  ZIP

3D  ZIP



Schematic light drawing



Photometric

|                          |                               |
|--------------------------|-------------------------------|
| Lighting type            | Direct                        |
| Light distribution       | Symmetric                     |
| CCT (K)                  | 2700                          |
| CRI>                     | 90                            |
| LED Life / Failure Ratio | L80B50 > 50.000h<br>(Tc=85°C) |
| Beam angle C0-180 (°)    | 45                            |
| Beam angle C90-270 (°)   | 45                            |
| Extreme cut off          | No                            |
| UGRL                     | <10                           |

Electrical

|                    |                   |
|--------------------|-------------------|
| Insulation class   | II                |
| Frequency (Hz)     | 50/60             |
| Main voltage (Vac) | 220-240           |
| Power supply       | Remote included   |
| Dimmable           | Yes               |
| Power supply type  | Mains Cut Dimming |

Notes