

Light Shadow Fixed No Trim 2 Spots Optic Wide Flood - Non IC

Designed by FLOS Architectural, 2022



LED - Power LED - 7W - 524lm - 3000K - CRI> 90 - Beam° 44

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	7
System power (W)	7
Source flux (lm)	636
System flux (lm)	524
Efficacy (lm/W)	74

Physical

Color	White/Black
Trim	No
Orientation	Fixed
IP internal	20
IP external	55



Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Ecodesign and Energy
Labelling

Replaceable (LED only)
light source by a
professional

Replaceable control
gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B10 > 50.000h
Beam angle C0-180 (°)	44
Beam angle C90-270 (°)	43
Extreme cut off	No
UGRL	<10

Electrical

Forward voltage (V)	7
LED current (mA)	900
Driver	Integral - Splice Box
Dimmable	Yes
Dimming type	Dimmable 0-10V, Dimmable ELV
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes

It requires a pre-installation frame, to be ordered separately.

Accessories & Power Supply



REQUIRED
Frame

ACCESSORYTYPE2

08.0510.00.90
Light Shadow 2 Spots 5/8" Frame
Fixed Trimless



REQUIRED
Power supply

SP20W900MA-120-C01
Splice Box 9"x2.22"x1.25", 900mA
, 20W, 0-10V Dimmable, Thermal
120V



REQUIRED
Power supply

SP20W900MA-277-C01
Splice Box 9"x2.22"x1.25", 900mA
, 20W, 0-10V Dimmable, Thermal
277V



REQUIRED
Power supply

SP20W900MA-ELV-C01
Splice Box 9"x2.22"x1.25", 900mA
, 20W, ELV Dimmable, Thermal
120V



OPTIONAL
Accessory

ACCESSORYTYPE2

08.0052.90
Accessory for mounting of No
Trim Fix continuous line.



OPTIONAL
Housing and Hanger Bar

TRAY-0032
Registration Tray - non electrical,
place holder for non IC new
construction, for Light Shadow Fix
2 Lights Trimless Fixed 2 Lights
Trimless