

## Light Shadow Fixed No Trim 8 Spots Optic Medium

Designed by FLOS Architectural, 2022

LED - Power LED - 21.6W - 2045lm - 2700K - CRI> 90 - Beam° 23

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 21.6                |
| System power (W)       | 21.6                |
| Source flux (lm)       | 2384                |
| Lumen Output (lm)      | 2045                |
| Efficacy (lm/W)        | 94                  |

### Physical

|                     |              |
|---------------------|--------------|
| Colour              | White/Bronze |
| Trim                | No           |
| Orientation         | Fixed        |
| Recessed depth (mm) | 75           |
| Length (mm)         | 280          |
| Net weight (kg)     | 0.5          |
| Package height (mm) | 10           |
| Package width (mm)  | 13           |
| IP internal         | 20           |
| IP external         | 55           |

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)


### Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional

 Replaceable control gear by a professional



Schematic light drawing



Photometric

|                          |                           |
|--------------------------|---------------------------|
| Lighting type            | Direct                    |
| Light distribution       | Symmetric                 |
| CCT (K)                  | 2700                      |
| CRI>                     | 90                        |
| McAdam steps (SDCM)      | 3                         |
| LED Life / Failure Ratio | L80B20 >50.000h (Tc=85°C) |
| Beam angle C0-180 (°)    | 23                        |
| Beam angle C90-270 (°)   | 23                        |
| Extreme cut off          | No                        |
| UGRL                     | <10                       |

Electrical

|                     |                 |
|---------------------|-----------------|
| Insulation class    | II              |
| Frequency (Hz)      | 50/60           |
| Forward voltage (V) | 3               |
| LED current (mA)    | 900             |
| Power supply        | Remote included |
| Dimmable            | No              |
| Power supply type   | Non Dimmable    |

Notes

Accessories & Power Supply



REQUIRED  
Frame

ACCESSORYTYPE2

08.0512.00

Pre-installation No Trim Frame 8L  
Fix



OPTIONAL  
Accessory

ACCESSORYTYPE2

08.0052.90

Accessory for mounting of No  
Trim Fix continuous line.