

Light Shadow Fixed No Trim 8 Spots Optic Medium - Non IC

Designed by FLOS Architectural, 2022




LED - Power LED - 22W - 2200lm - 3000K - CRI> 90 - Beam° 23

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	22
System power (W)	21.6
Source flux (lm)	2544
System flux (lm)	2200
Efficacy (lm/W)	101

Physical

Color	Black/Steel
Trim	No
Orientation	Fixed
Net weight (lb)	1.11
Gross weight (lb)	1.36
Package volume (in)	122.04
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	---------------------

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Ecodesign and Energy
Labelling

Replaceable (LED only)
light source by a
professional

Replaceable control
gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B20 >50.000h (Tc=85°C)
Beam angle C0-180 (°)	23
Beam angle C90-270 (°)	22
Extreme cut off	No
UGRL	<10

Electrical

Forward voltage (V)	25.8
LED current (mA)	900
Driver	Integral - Splice Box
Dimmable	Yes
Dimming type	Dimmable 0-10V, Dimmable ELV
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes

It requires a pre-installation frame, to be ordered separately.

Accessories & Power Supply




REQUIRED
Frame
ACCESSORYTYPE2


08.0512.00.90
Light Shadow 8 Spots 5/8" Frame
Fixed Trimless



REQUIRED
Power supply
SP25W900MA-120-A01
Splice Box 9"x3.59"x1.25", 900mA
, 25W, 0-10V Dimmable, Thermal
120V



REQUIRED
Power supply
SP25W900MA-277-A01
Splice Box 9"x3.59"x1.25", 900mA
, 25W, 0-10V Dimmable, Thermal
277V



REQUIRED
Power supply
SP30W900MA-ELV-U01
Splice Box 7"x3.59"x1.25", 900mA
, 30W, ELV Dimmable, Thermal
120V



OPTIONAL
Accessory
ACCESSORYTYPE2

08.0052.90
Accessory for mounting of No
Trim Fix continuous line.