


## Light Shadow Fixed No Trim Dali Version 4 Spots Square Optic Flood

Designed by FLOS Architectural, 2022



947lm - 2700K - CRI> 90 - Beam° 35

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V). It requires a pre-installation frame, to be ordered separately.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Number of lamps        | 1                   |
| System power (W)       | 10.8                |
| Source flux (lm)       | 1169                |
| Lumen Output (lm)      | 947                 |
| Efficacy (lm/W)        | 87                  |

### Physical

|                     |             |
|---------------------|-------------|
| Colour              | White/Steel |
| Trim                | No          |
| Orientation         | Fixed       |
| Net weight (kg)     | 0.34        |
| Package height (mm) | 16          |
| Package width (mm)  | 14          |
| Package length (mm) | 21          |
| IP internal         | 20          |
| IP external         | 55          |

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)




### Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

## Schematic light drawing



### Photometric

|                          |                               |
|--------------------------|-------------------------------|
| Lighting type            | Direct                        |
| Light distribution       | Symmetric                     |
| CCT (K)                  | 2700                          |
| CRI>                     | 90                            |
| LED Life / Failure Ratio | L80B10 > 50.000h<br>(Tc=85°C) |
| Beam angle C0-180 (°)    | 35                            |
| Beam angle C90-270 (°)   | 35                            |
| Extreme cut off          | No                            |
| UGR <sub>L</sub>         | <10                           |

### Electrical

|                    |                 |
|--------------------|-----------------|
| Insulation class   | II              |
| Frequency (Hz)     | 50/60           |
| Main voltage (Vac) | 220-240         |
| LED current (mA)   | 900             |
| Power supply       | Remote included |
| Dimmable           | Yes             |
| Power supply type  | Dimmable DALI 2 |

## Accessories & Power Supply



### REQUIRED Frame

08.0269.00

Pre-installation frame for Light  
Shadow Fixed No Trim 4 Spots  
Square



### OPTIONAL

08.0270.00

Accessory for mounting of No  
Trim continuous line for Light  
Shadow Fixed 4 Spots Square