

# FLOS

05.1332.14CUQ Black/Bronze

## Light Shadow Fixed Trim 12 Spots Optic Wide Flood - Non IC

Designed by FLOS Architectural


LED - Power LED - 34W - 2969lm - 2700K - CRI> 90 - Beam° 46

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 34                  |
| System power (W)       | 32.4                |
| Source flux (lm)       | 3576                |
| System flux (lm)       | 2969                |
| Efficacy (lm/W)        | 91                  |

### Physical

|                     |              |
|---------------------|--------------|
| Color               | Black/Bronze |
| Trim                | Yes          |
| Orientation         | Fixed        |
| Net weight (lb)     | 1.46         |
| Gross weight (lb)   | 1.7          |
| Package volume (in) | 305.1        |
| IP internal         | 20           |

### Download

|                       |     |
|-----------------------|-----|
| Family spec sheet     | ZIP |
| Mounting instructions | PDF |

### Photometric Files


|           |     |
|-----------|-----|
| LDT / IES | ZIP |
|-----------|-----|

### Technical Drawings

|    |     |
|----|-----|
| 2D | ZIP |
| 3D | ZIP |



Schematic light drawing



### Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Photometric

|                          |                          |
|--------------------------|--------------------------|
| Lighting type            | Direct                   |
| Light distribution       | Symmetric                |
| CCT (K)                  | 2700                     |
| CRI>                     | 90                       |
| LED Life / Failure Ratio | L80B50>50.000h (Tc=85°C) |
| Beam angle C0-180 (°)    | 46                       |
| Beam angle C90-270 (°)   | 46                       |
| Extreme cut off          | No                       |
| UGRL                     | <10                      |

Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Forward voltage (V) | 38.7                                  |
| LED current (mA)    | 900                                   |
| Driver              | Integral - Splice Box                 |
| Dimmable            | Yes                                   |
| Dimming type        | Dimmable 1-10V                        |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |

Notes

Pre-Installation frame not required.

Accessories & Power Supply



REQUIRED  
Power supply

SP40W900MA-120-A01  
Splice Box 7"x3.59"x1.25", 900mA ,  
40W, 0-10V Dimmable, Thermal  
120V



REQUIRED  
Power supply

SP40W900MA-277-A01  
Splice Box 7"x3.59"x1.25", 900mA ,  
40W, 0-10V Dimmable, Thermal  
277V