

Light Shadow Fixed Trim 8 Spots Optic Flood

Designed by FLOS Architectural, 2022

LED - Power LED - 21.6W - 2023lm - 2700K - CRI> 90 - Beam° 29



Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Download

Mounting instructions

[↓ PDF](#)



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	21.6
System power (W)	21.6
Source flux (lm)	2384
Lumen Output (lm)	2023
Efficacy (lm/W)	93


Physical

Colour	Black/Steel
Trim	Yes
Orientation	Fixed
Recessed depth (mm)	75
Length (mm)	287
Net weight (kg)	0.5
Package height (mm)	10
Package width (mm)	13
IP internal	20
IP external	55

Ecodesign and Energy Labelling



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
LED Life / Failure Ratio	L80B50 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	29
Beam angle C90-270 (°)	28
Extreme cut off	No
UGRL	<10

Electrical

Insulation class	II
Frequency (Hz)	50/60
Forward voltage (V)	3
LED current (mA)	900
Power supply	Remote included
Dimmable	No
Power supply type	Non Dimmable

Notes