

05.1217.14CUQ Black/Bronze

Light Shadow Fixed Trim 8 Spots Optic Medium - Non IC

Designed by FLOS Architectural




LED - Power LED - 22W - 2182lm - 3000K - CRI> 90 - Beam° 23

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	22
System power (W)	21.6
Source flux (lm)	2544
System flux (lm)	2182
Efficacy (lm/W)	101

Physical

Color	Black/Bronze
Trim	Yes
Orientation	Fixed
Net weight (lb)	1.11
Gross weight (lb)	1.36
Package volume (in)	122.04
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C)
Beam angle C0-180 (°)	23
Beam angle C90-270 (°)	23
Extreme cut off	No
UGRL	<10

Electrical

Forward voltage (V)	25.8
LED current (mA)	900
Driver	Integral - Splice Box
Dimmable	Yes
Dimming type	Dimmable 0-10V, Dimmable ELV
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes

Pre-Installation frame not required.

<https://professional.flos.com/en-US/us/product/light-shadow-fixed-trim-8-spots-optic-medium-non-ic-05.1217.14cuq/>

05.1217.14CUQ

©2026 Flos - P.IVA 00290820174 - 9/18/2026

professional.flos.com | info@flos.com 2/3

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order to improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Accessories & Power Supply



REQUIRED
Power supply

SP25W900MA-120-A01

Splice Box 9"x3.59"x1.25", 900mA
, 25W, 0-10V Dimmable, Thermal
120V



REQUIRED
Power supply

SP25W900MA-277-A01

Splice Box 9"x3.59"x1.25", 900mA
, 25W, 0-10V Dimmable, Thermal
277V



REQUIRED
Power supply

SP30W900MA-ELV-U01

Splice Box 7"x3.59"x1.25", 900mA ,
30W, ELV Dimmable, Thermal
120V