

## Light Shadow Fixed Trim Mains dimming Version 2 Spots Optic Medium

Designed by FLOS Architectural, 2022

6.5W - 511lm - 2700K - CRI> 90 - Beam° 23

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Number of lamps        | 1                   |
| Power (W)              | 6.5                 |
| System power (W)       | 7                   |
| Source flux (lm)       | 596                 |
| Lumen Output (lm)      | 511                 |
| Efficacy (lm/W)        | 73                  |

### Physical

|                     |              |
|---------------------|--------------|
| Colour              | White/Bronze |
| Trim                | Yes          |
| Orientation         | Fixed        |
| Recessed depth (mm) | 75           |
| Length (mm)         | 77           |
| Net weight (kg)     | 0.25         |
| IP internal         | 20           |
| IP external         | 55           |

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files


LDT / IES [↓ ZIP](#)


### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)


### Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional

 Replaceable control gear by a professional



Schematic light drawing



Photometric

|                          |                               |
|--------------------------|-------------------------------|
| Lighting type            | Direct                        |
| Light distribution       | Symmetric                     |
| CCT (K)                  | 2700                          |
| CRI>                     | 90                            |
| LED Life / Failure Ratio | L80B50 > 50.000h<br>(Tc=85°C) |
| Beam angle C0-180 (°)    | 23                            |
| Beam angle C90-270 (°)   | 23                            |
| Extreme cut off          | No                            |
| UGRL                     | <10                           |

Electrical

|                    |                   |
|--------------------|-------------------|
| Insulation class   | II                |
| Frequency (Hz)     | 50/60             |
| Main voltage (Vac) | 220-240           |
| LED current (mA)   | 900               |
| Power supply       | Remote included   |
| Dimmable           | Yes               |
| Power supply type  | Mains Cut Dimming |

Notes