

Light Shadow Fixed Trim Mains dimming Version 8 Spots Optic Wide Flood

Designed by FLOS Architectural, 2022

20.9W - 1681lm - 2700K - CRI> 90 - Beam° 46

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
Number of lamps	1
Power (W)	20.9
System power (W)	18
Source flux (lm)	2024
Lumen Output (lm)	1681
Efficacy (lm/W)	93

Physical

Colour	Black/Bronze
Trim	Yes
Orientation	Fixed
Recessed depth (mm)	75
Length (mm)	287
Net weight (kg)	0.5
IP internal	20
IP external	55

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D




3D



Ecodesign and Energy Labelling




Replaceable (LED only)
light source by a
professional



Replaceable control
gear by a professional



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
LED Life / Failure Ratio	L80B50 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	46
Beam angle C90-270 (°)	46
Extreme cut off	No
UGRL	<10

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
LED current (mA)	900
Power supply	Remote included
Dimmable	Yes
Power supply type	Mains Cut Dimming

Notes