

Light Shadow Mini Adjustable No Trim 4 Spots Optic Flood

Designed by FLOS Architectural, 2025



LED - Power LED - 3.9W - 343lm - 2700K - CRI> 90 - Beam° 37

Adjustable recessed luminaire with 2 LED lighting spots. Remote power supply not included (220-240V). It requires a pre-installation frame, to be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	3.9
System power (W)	6.2
Source flux (lm)	380
System flux (lm)	343

Physical

Color	White/White
Orientation	Adjustable
Net weight (lb)	0.4
Gross weight (lb)	0.5
Package height (in)	0.3
Package width (in)	0.6
Package length (in)	0.3
IP internal	20

Download

Mounting instructions  PDF

Photometric Files

LDT / IES  SVG

Technical Drawings

2D  ZIP

3D  ZIP

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **G**




REPLACEABLE2



PWRSUPRPL2



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	93
Rg gamut index	98
LED Life / Failure Ratio	L90B20>52.000h_Tc85°C
Beam angle C0-180 (°)	37
Beam angle C90-270 (°)	38
UGRL	<10

Electrical

Insulation class	III
Forward voltage (V)	6
LED current (mA)	400
Driver	Remote
Dimmable	Yes
Dimming type	Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No