

# FLOS

05.8416.40 White


## Light Shadow Mini Dots - Single Spot Module. Set of 2 Spots Optic Medium

Designed by FLOS Architectural, 2025



LED - Power LED - 1.5W - 139lm - 3000K - CRI> 90

LED lighting luminaire to be inserted in the recessed frames (Trim/NoTrim). It requires a pre-installation frame, to be ordered separately. Installation through a bayonet system with interchangeable spots. Available in one-light versions and groups of two and four lights. Driver not included.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Recessed            |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 1.5                 |
| System power (W)       | 2.3                 |
| Source flux (lm)       | 155                 |
| Lumen Output (lm)      | 139                 |

### Physical

|                     |       |
|---------------------|-------|
| Colour              | White |
| Orientation         | Fixed |
| Recessed depth (mm) | 42    |
| Spot diameter (mm)  | 20    |
| Length (mm)         | 20    |
| Canopy width (mm)   | 0     |
| Canopy height (mm)  | 0     |
| Net weight (kg)     | 0.04  |
| Package height (mm) | 6     |
| Package width (mm)  | 13    |
| Package length (mm) | 7     |
| IP internal         | 20    |
| IP external         | 54    |

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files


LDT / IES [↓ ZIP](#)

### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)


### Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional

 Replaceable control gear by a professional



## Schematic light drawing



### Photometric

|                          |                       |
|--------------------------|-----------------------|
| Lighting type            | Direct                |
| Light distribution       | Symmetric             |
| CCT (K)                  | 3000                  |
| CRI>                     | 90                    |
| McAdam steps (SDCM)      | 3                     |
| Rf fidelity index        | 91                    |
| Rg gamut index           | 101                   |
| LED Life / Failure Ratio | L90B20>52.000h_Tc85°C |
| Extreme cut off          | Yes                   |

### Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Insulation class    | III                                   |
| Forward voltage (V) | 3                                     |
| LED current (mA)    | 500                                   |
| Power supply        | Remote                                |
| Dimmable            | Yes                                   |
| Power supply type   | Dimmable                              |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |
| Batteries inside    | No                                    |

## Accessories & Power Supply



REQUIRED  
Power supply

Electrical

60.9207

Casambi continuous current power supply, dimmable 220/240V - 50/60Hz, 300mA - 16W / 350mA - 18,5W / 400mA - 21,5W / 450 mA - 24W / 500mA - 27W / 600mA - 32W / 650 mA - 35W / 700 mA - 36W / 750 / 800 / 900 / 1000 / 1050 / 1200 mA - 38W.



REQUIRED  
Power supply

Electrical

60.9188

Continuous current power supply of 13-20W, 110\*/240V - 50/60Hz with current selected through adjustable 200 mA - 13W / 300 mA - 15W / 350 mA - 18W / 400 / 450 / 500 / 550 / 600 / 650 / 700 / 750 / 800 / 850 / 900 mA - 20W. switch. 0/1-10V or push.



REQUIRED  
Power supply

Electrical

60.9439

Continuous current power supply, 0/1-10V dimmable, 220/240V - 50/60Hz, 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700 / 750 / 800 / 900 / 950 / 1000 / 1050mA-36W



REQUIRED  
Power supply

Electrical

60.9467

Mains dimming 20W Constant current power supply, AC phase-cut adjustable, trailing & leading edge dimming, 220/240V - 50/60Hz, with dip-switch programmable power supply current. Output current: 900mA - 20W / 850mA - 20W / 800mA - 20W / 750mA - 20W / 70...



REQUIRED  
Frame

Mounting

08.1050.00

Frame No Trim for Light Shadow Mini Dots 1L



REQUIRED  
Frame

Mounting

08.1053.14

Frame Trim for Light Shadow Mini Dots 1L



REQUIRED  
Frame

Mounting

08.1053.40

Frame Trim for Light Shadow Mini Dots 1L



REQUIRED  
Power supply

Electrical

60.7887

Constant current power supply 3W, 220-240V - 50/60Hz fixed supply current. Non-dimmable. Output current: 2.25W - 500mA



REQUIRED  
Power supply

Electrical

60.9874.0500

Continuous current supply source  
of 220-240V - 50/60Hz - 500mA  
15W with dimmable Casambi



REQUIRED  
Power supply

Electrical

60.9957.0500

Continuous current supply source  
of 220-240V - 50/60Hz -  
500mA.with dimmable Dali 2



REQUIRED  
Power supply

Electrical

60.7744

Continuous current supply source  
of 220-240V - 50/60Hz - 350mA  
4,5W - 500mA 6,5W - 600mA  
7,5W - 700mA 9W selectable by  
swtich, dimmable Dali 2 & Push



REQUIRED  
Power supply

Electrical

60.9954.0500

Continuous current supply source  
of 220-240V - 50/60Hz - 500mA  
25W, Non dimmable



OPTIONAL  
Accessory

08.1062.90

Extraction tool for Light Shadow  
Mini Dots