



05.8545.14.9S Black/White

Light Shadow Mini Fixed No Trim 2 Spots Optic Medium

Designed by FLOS Architectural, 2025



LED - Power LED - 2.2W - 175lm - 2700K - CRI> 90 - Beam° 26

Fixed recessed luminaire with 2 LED lighting spots. Remote power supply not included (220-240V).It requires a pre-installation frame,to be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	2.2
System power (W)	3.4
Source flux (lm)	190
System flux (lm)	175

Physical

Color	Black/White
Orientation	Fixed
Net weight (lb)	0.2
Gross weight (lb)	0.3
Package height (in)	0.3
Package width (in)	0.6
Package length (in)	0.3
IP internal	20
IP external	54

Download

Mounting instructions  PDF

Photometric Files

LDT / IES  ZIP


Technical Drawings

2D  ZIP


3D  ZIP

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	93
Rg gamut index	98
LED Life / Failure Ratio	L90B20>52.000h_Tc85°C
Beam angle C0-180 (°)	26
Beam angle C90-270 (°)	26
UGRL	<10

Electrical

Insulation class	III
Forward voltage (V)	6
LED current (mA)	400
Driver	Remote
Dimmable	Yes
Dimming type	Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Accessories & Power Supply



REQUIRED
Frame

ACCESSORYTYPE3

08.1056.00
Pre-installation Light Shadow Mini
No Trim Frame 2L Fix



REQUIRED
Power supply

ACCESSORYTYPE1

SP10W300MA-DAL-Y1
Splice Box UL DALI & PUSH
Dimmable 300mA LED Driver
10W Size: 7" x 2.2" x 1.2"



REQUIRED
Power supply

ACCESSORYTYPE1

SP10W300MA-VAR-Y1
Splice Box UL TRIAC & 0-10V
Dimmable 300mA LED Driver
10W Size: 7" x 2.2" x 1.2"