

Light Shadow Mini Fixed Trim 4 Spots Optic Flood

Designed by FLOS Architectural, 2025

LED - Power LED - 3.9W - 352lm - 3000K - CRI> 90 - Beam° 37



Fixed recessed luminaire with 4 LEDlighting spots. Remote power supply not included (240-240V). No pre-installation frame required.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	3.9
System power (W)	6.2
Source flux (lm)	400
System flux (lm)	352

Physical

Color	White/Black
Orientation	Fixed
Net weight (lb)	0.3
Gross weight (lb)	0.4
Package height (in)	0.3
Package width (in)	0.6
Package length (in)	0.3
IP internal	20
IP external	54

Download

Mounting instructions

PDF

Photometric Files

LDT / IES

SVG

Technical Drawings

2D

ZIP

3D

ZIP

Ecodesign and Energy Labelling


This product contains a light source of energy efficiency class G

REPLACEABLE2

PWRSUPRPL2



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	91
Rg gamut index	101
LED Life / Failure Ratio	L90B20>52.000h_Tc85°C
Beam angle C0-180 (°)	37
Beam angle C90-270 (°)	38
UGRL	<10

Electrical

Insulation class	III
Forward voltage (V)	6
LED current (mA)	300
Driver	Remote
Dimmable	Yes
Dimming type	Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No