

## Light Shadow Mini Round Trim Optic Flood

Designed by FLOS Architectural, 2025

LED - Power LED - 2.2W - 439lm - 3000K - CRI> 90 - Beam° 39



Recessed integrated luminaire with 7 LED lighting spots. Remote power supply not included (220-240V). Pre-installation frame not required.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Recessed            |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 2.2                 |
| System power (W)       | 5.4                 |
| Source flux (lm)       | 504                 |
| System flux (lm)       | 439                 |

### Physical

|                     |              |
|---------------------|--------------|
| Color               | White/Bronze |
| Orientation         | Fixed        |
| Net weight (lb)     | 0.3          |
| Gross weight (lb)   | 0.4          |
| Package height (in) | 0.4          |
| Package width (in)  | 0.6          |
| Package length (in) | 0.4          |
| IP internal         | 20           |
| IP external         | 54           |

Download

Mounting instructions

ZIP

Photometric Files

LDT / IES

ZIP

Technical Drawings

2D

ZIP

3D

ZIP

Ecodesign and Energy Labelling


This product contains a light source of energy efficiency class G

REPLACEABLE2

PWRSUPRPL2



Schematic light drawing



Photometric

|                          |                       |
|--------------------------|-----------------------|
| Lighting type            | Direct                |
| Light distribution       | Symmetric             |
| CCT (K)                  | 3000                  |
| CRI>                     | 90                    |
| McAdam steps (SDCM)      | 3                     |
| Rf fidelity index        | 91                    |
| Rg gamut index           | 101                   |
| LED Life / Failure Ratio | L90B50>59.000h_Tc85°C |
| Beam angle C0-180 (°)    | 39                    |
| Beam angle C90-270 (°)   | 39                    |
| UGRL                     | <10                   |

Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Insulation class    | III                                   |
| Forward voltage (V) | 21                                    |
| LED current (mA)    | 200                                   |
| Driver              | Remote                                |
| Dimmable            | Yes                                   |
| Dimming type        | Dimmable                              |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |
| Batteries inside    | No                                    |

Accessories & Power Supply



REQUIRED  
Power supply

ACCESSORYTYPE1

SP10W200MA-VAR-Y1  
Splice Box UL TRIAC & 0-10V  
Dimmable 200mA LED Driver  
10W Size: 7" x 2.2" x 1.2"

REQUIRED  
Power supply

ACCESSORYTYPE1

SP10W200MA-DAL-Y1  
Splice Box UL DALI & PUSH  
Dimmable 200mA LED Driver  
10W Size: 7" x 2.2" x 1.2"