

Light Shadow Optic Flood Dali Version

Designed by FLOS Architectural, 2018




LED - Power LED - 10.8W - 1052lm - 3000K - CRI> 90

LED lighting module, with 4 spotlights and low glare, to be installed in the The Running Magnet system. DC/DC, built-in electronic current converter.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Power (W)	10.8
System power (W)	0
Source flux (lm)	1272
System flux (lm)	1052
Efficacy (lm/W)	98

Physical

Color	White/Black
Orientation	Fixed
Length (in)	5.51
Net weight (lb)	0.74
Gross weight (lb)	1.01
IP internal	20

Download

- [Family spec sheet](#)  ZIP
- [Mounting instructions](#)  PDF

Photometric Files


- [LDT / IES](#)  ZIP

Technical Drawings

- [2D](#)  ZIP
- [3D](#)  ZIP



Schematic light drawing



Ecodesign and Energy
Labelling

Replaceable (LED only)
light source by a
professional

Replaceable control
gear by a professional

Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50>50.000h_(Tc=85°C)
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	900
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable DALI 2
Dimming range (%)	10-100
Dimming interface	Remote Dimmable (Dimmer Not Included)