

Light Shadow Optic Flood On Board Dimmer

Designed by FLOS Architectural, 2018




10.8W - 1052lm - 3000K - CRI> 90

LED lighting module, with 4 spotlights and low glare, to be installed in the The Running Magnet system. DC/DC, built-in electronic current converter.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	10.8
System power (W)	0
Source flux (lm)	1272
System flux (lm)	1052
Efficacy (lm/W)	98

Physical

Color	Black/Black
Net weight (lb)	0.75
Gross weight (lb)	1.02
Package height (in)	#VALUE!
Package width (in)	#VALUE!
Package length (in)	#VALUE!
Package volume (in)	62
IP internal	20

Download

Family spec sheet	Download ZIP
Mounting instructions	Download PDF

Photometric Files


LDT / IES	Download ZIP
-----------	------------------------------

Technical Drawings

2D	Download ZIP
3D	Download ZIP



Schematic light drawing



Photometric

CCT (K)	3000
CRI>	90
Extreme cut off	No

Electrical

Insulation class	II
Forward voltage (V)	24
LED current (mA)	900
Dimmable	Yes
Dimming type	Dimmer on board