


## Light Shadow Optic Wide Flood 0-10V Dimmable


10.8W - 1056lm - 3000K - CRI> 90



LED lighting module, with 4 spotlights and low glare, to be installed in the The Running Magnet system. DC/DC, built-in electronic current converter.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                   |                     |
|-------------------|---------------------|
| Mounting          | Track               |
| Environments      | Indoor dry location |
| Light Source Type | LED                 |
| LED type          | Power LED           |
| Number of lamps   | 1                   |
| Power (W)         | 10.8                |
| System power (W)  | 0                   |
| Source flux (lm)  | 1272                |
| System flux (lm)  | 1056                |
| Efficacy (lm/W)   | 98                  |

### Physical

|                     |              |
|---------------------|--------------|
| Color               | White/Bronze |
| Trim                | No           |
| Orientation         | Fixed        |
| Net weight (lb)     | 0.75         |
| Gross weight (lb)   | 1.02         |
| Package volume (in) | 62           |
| IP internal         | 20           |

### Download

|                       |                              |
|-----------------------|------------------------------|
| Family spec sheet     | <a href="#">Download ZIP</a> |
| Mounting instructions | <a href="#">Download PDF</a> |

### Photometric Files


|           |                              |
|-----------|------------------------------|
| LDT / IES | <a href="#">Download ZIP</a> |
|-----------|------------------------------|

### Technical Drawings

|    |                              |
|----|------------------------------|
| 2D | <a href="#">Download ZIP</a> |
| 3D | <a href="#">Download ZIP</a> |



Schematic light drawing



Photometric

|                    |                |
|--------------------|----------------|
| Light distribution | Roto symmetric |
| CCT (K)            | 3000           |
| CRI>               | 90             |
| Extreme cut off    | No             |

Electrical

|                     |                |
|---------------------|----------------|
| Insulation class    | II             |
| Forward voltage (V) | 24             |
| LED current (mA)    | 900            |
| Dimmable            | Yes            |
| Dimming type        | Dimmable 0-10V |