

## Light Shadow Optic Wide Flood Dali Version

Designed by FLOS Architectural, 2018




LED - Power LED - 10.8W - 982lm - 2700K - CRI> 90

LED lighting module, with 4 spotlights and low glare, to be installed in the The Running Magnet system. DC/DC, built-in electronic current converter.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Power (W)              | 10.8                |
| System power (W)       | 0                   |
| Source flux (lm)       | 1192                |
| System flux (lm)       | 982                 |
| Efficacy (lm/W)        | 91                  |

### Physical

|                   |             |
|-------------------|-------------|
| Color             | White/Black |
| Orientation       | Fixed       |
| Length (in)       | 5.51        |
| Net weight (lb)   | 0.74        |
| Gross weight (lb) | 1.01        |
| IP internal       | 20          |

### Download

- [Family spec sheet](#)  ZIP
- [Mounting instructions](#)  PDF

### Photometric Files


- [LDT / IES](#)  ZIP

### Technical Drawings

- [2D](#)  ZIP
- [3D](#)  ZIP



Schematic light drawing



Ecodesign and Energy  
Labelling

Replaceable (LED only)  
light source by a  
professional

Replaceable control  
gear by a professional

Photometric

|                          |                          |
|--------------------------|--------------------------|
| Lighting type            | Direct                   |
| Light distribution       | Roto symmetric           |
| CCT (K)                  | 2700                     |
| CRI>                     | 90                       |
| McAdam steps (SDCM)      | 3                        |
| LED Life / Failure Ratio | L80B50>50.000h_(Tc=85°C) |
| Extreme cut off          | No                       |

Electrical

|                     |                                          |
|---------------------|------------------------------------------|
| Insulation class    | III                                      |
| Forward voltage (V) | 24                                       |
| LED current (mA)    | 900                                      |
| Driver              | Remote excluded                          |
| Dimmable            | Yes                                      |
| Dimming type        | Dimmable DALI 2                          |
| Dimming range (%)   | 10-100                                   |
| Dimming interface   | Remote Dimmable<br>(Dimmer Not Included) |