

FLOS



05.2710.14 Black/White

Light Shadow Pro Ø45 Surface Flood

Designed by FLOS Architectural, 2022




8.8W - 663lm - 2700K - CRI> 90 - Beam° 32

Luminaire with low glare for surface installation. Integrated 220-240 V power supply. IP54 watertightness.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|----------------------|
| Mounting | Ceiling surface |
| Environments | Indoor damp location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | LED array |
| Number of lamps | 1 |
| Power (W) | 8.8 |
| System power (W) | 11 |
| Source flux (lm) | 800 |
| Lumen Output (lm) | 663 |

Physical

| | |
|---------------------|-------------|
| Colour | Black/White |
| Orientation | Fixed |
| Spot diameter (mm) | 52 |
| Length (mm) | 52 |
| Net weight (kg) | 0.22 |
| Package height (mm) | 157 |
| Package width (mm) | 210 |
| Package length (mm) | 135 |
| IP internal | 54 |

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[🔒 Bim](#) [↓ ZIP](#)



Schematic light drawing



Beam Angle: 33°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 2172 | 0.58 |
| 2 | 543 | 1.17 |
| 3 | 241 | 1.75 |
| 4 | 136 | 2.34 |
| 5 | 87 | 2.92 |

Luminous flux luminaire
663 lm (EXTREME CUT OFF)

Photometric

| | |
|--------------------------|-----------------------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 2700 |
| CRI> | 90 |
| McAdam steps (SDCM) | 2 |
| Rf fidelity index | 93 |
| Rg gamut index | 99 |
| LED Life / Failure Ratio | L90B10_33.000_Tc=85°C |
| Beam angle C0-180 (°) | 32 |
| Beam angle C90-270 (°) | 32 |
| UGR _L | <10 |

Electrical

| | |
|---------------------|--------------|
| Insulation class | I |
| Frequency (Hz) | 50-60 |
| Main voltage (Vac) | 220-240 |
| Forward voltage (V) | 36.1 |
| LED current (mA) | 250 |
| Power supply | Integrated |
| Dimmable | No |
| Power supply type | Non Dimmable |
| Precabled | No |

Ecodesign and Energy

Labelling

