

Light Shadow Pro Ø 90 Wall-Washer - Non IC

Designed by FLOS Architectural



LED - LED array - 14.8W - 1077lm - 2700K - CRI> 90 - Beam° 23

LED lighting module, with wall washer optic, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Remote driver not included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	14.8
Source flux (lm)	1590
System flux (lm)	1077

Physical

Color	Bronze
Orientation	Directional
Net weight (lb)	0.89
Gross weight (lb)	1.55
Package volume (in)	427.14
IP internal	20
IP external	54

Download

Mounting instructions



Photometric Files

LDT / IES



Ecodesign and Energy Labelling




REPLACEABLE2



PWRSUPRPL2



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	2
LED Life / Failure Ratio	L70B40 >50.000h (Tc=85°C)
Beam angle C0-180 (°)	23
Beam angle C90-270 (°)	23
UGRL	<19

Electrical

Forward voltage (V)	74
LED current (mA)	400
Driver	Attached Splice Box
Dimmable	Yes
Dimming type	Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes


Class 2 Listed.

Accessories & Power Supply




REQUIRED
Power supply

SP30W400MA-120-U01
Splice Box 7"x2.22"x1.25", 400mA ,
30W, 0-10V Dimmable, Thermal
120V



REQUIRED
Power supply

SP30W400MA-277-U01
Splice Box 7"x2.22"x1.25", 400mA ,
30W, 0-10V Dimmable, Thermal
277V



REQUIRED
Power supply

SP30W400MA-ELV-U01
Splice Box 7"x2.22"x1.25", 400mA ,
30W, ELV Dimmable, Thermal
120V




REQUIRED
Frame

08.0161.40
Installation Frame Trim Ø90 Fix




REQUIRED
Frame

08.0161.14
Installation Frame Trim Ø90 Fix




REQUIRED
Frame

08.0193.00
Installation Frame No Trim Ø90
Fix



OPTIONAL
Housing and Hanger Bar

TRAY-0016
Registration Tray - non electrical,
place holder for non IC new
construction Round, Ø4""



OPTIONAL
Housing and Hanger Bar

TRAY-0019
Registration Tray - non electrical,
place holder for non IC new
construction, Ø4.75"