

## Light Shadow Spot 30 Dali Dimmable

Designed by FLOS Architectural, 2023



4W - 246lm - 2700K - CRI> 90 - Beam° 33

LED projection lighting module for installation in the Zero Track Pro system.  
Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Number of lamps        | 1                   |
| Power (W)              | 4                   |
| System power (W)       | 4.7                 |
| Source flux (lm)       | 298                 |
| System flux (lm)       | 246                 |
| Efficacy (lm/W)        | 52                  |

### Physical

|                          |               |
|--------------------------|---------------|
| Color                    | Brushed Steel |
| Orientation              | Adjustable    |
| Rotation (°)             | 360           |
| Longitudinal tilting (°) | 90            |
| IP internal              | 20            |

### Download

|                       |                     |
|-----------------------|---------------------|
| Family spec sheet     | <a href="#">ZIP</a> |
| Family spec sheet     | <a href="#">ZIP</a> |
| Mounting instructions | <a href="#">PDF</a> |

### Photometric Files

|           |                     |
|-----------|---------------------|
| LDT / IES | <a href="#">ZIP</a> |
|-----------|---------------------|

### Technical Drawings

|    |                     |
|----|---------------------|
| 2D | <a href="#">ZIP</a> |
| 3D | <a href="#">ZIP</a> |

### Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G




REPLACEABLE2



PWRSUPRPL2



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 2700      |
| CRI>                   | 90        |
| McAdam steps (SDCM)    | 2         |
| Beam angle C0-180 (°)  | 33        |
| Beam angle C90-270 (°) | 33        |
| Extreme cut off        | No        |
| UGRL                   | <10       |

Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Insulation class    | III                                   |
| Forward voltage (V) | 24                                    |
| LED current (mA)    | 900                                   |
| Driver              | Remote excluded                       |
| Dimmable            | Yes                                   |
| Dimming type        | Dimmable DALI 2                       |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |