

Light Shadow Spot 30 Non Dimmable

Designed by FLOS Architectural, 2023



4W - 274lm - 3000K - CRI> 90 - Beam° 22

LED projection lighting module for installation in the Zero Track Pro system.
Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	4
System power (W)	4.7
Source flux (lm)	318
System flux (lm)	274
Efficacy (lm/W)	58

Physical

Color	Brushed Bronze
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
IP internal	20

Download

Family spec sheet	ZIP
Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files

LDT / IES	ZIP
-----------	---------------------

Technical Drawings

2D	ZIP
3D	ZIP

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G




REPLACEABLE2



PWRSUPRPL2



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	2
Beam angle C0-180 (°)	22
Beam angle C90-270 (°)	22
Extreme cut off	No
UGRL	<10

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	900
Driver	Remote excluded
Dimmable	No
Dimming interface	Remote Dimmable (Dimmer Not Included)