

## Light Shadow Spot 45 Dali Dimmable

Designed by FLOS Architectural, 2023



10W - 650lm - 2700K - CRI> 90 - Beam° 15

LED projection lighting module for installation in the Zero Track Pro system.  
Electronic DC/DC converter incorporated. Individual control via DALI protocol and  
broadcast mode via 1-10V.

Are you a professional and your project needs  
consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Number of lamps        | 1                   |
| Power (W)              | 10                  |
| Source flux (lm)       | 799                 |
| System flux (lm)       | 650                 |
| Efficacy (lm/W)        | 65                  |

### Physical

|                          |            |
|--------------------------|------------|
| Color                    | White      |
| Orientation              | Adjustable |
| Rotation (°)             | 360        |
| Longitudinal tilting (°) | 90         |
| IP internal              | 20         |

### Download

|                       |     |
|-----------------------|-----|
| Family spec sheet     | ZIP |
| Family spec sheet     | ZIP |
| Mounting instructions | PDF |

### Photometric Files

|           |     |
|-----------|-----|
| LDT / IES | ZIP |
|-----------|-----|

### Technical Drawings

|    |     |
|----|-----|
| 2D | ZIP |
| 3D | ZIP |

### Ecodesign and Energy Labelling

This product contains a light  
source of energy efficiency  
class G




REPLACEABLE2



PWRSUPRPL2



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 2700      |
| CRI>                   | 90        |
| McAdam steps (SDCM)    | 2         |
| Beam angle C0-180 (°)  | 15        |
| Beam angle C90-270 (°) | 15        |
| Extreme cut off        | No        |
| UGRL                   | <10       |

Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Insulation class    | III                                   |
| Forward voltage (V) | 24                                    |
| LED current (mA)    | 700                                   |
| Driver              | Remote excluded                       |
| Dimmable            | Yes                                   |
| Dimming type        | Dimmable DALI 2                       |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |