

# FLOS

05.9035.14A Black

## Light Shadow Spot 45 Dimmer On Board

Designed by FLOS Architectural, 2022



739lm - Beam° 15

LED accent lighting module for installation in The Tracking Magnet or Infra-Structure systems. For wireless control of luminaires, please select Casambi integrated versions. Accessories available, (honeycomb and CCT dichroic filters).

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | LED array           |
| Number of lamps        | 1                   |
| System power (W)       | 10                  |
| Source flux (lm)       | 909                 |
| Lumen Output (lm)      | 739                 |
| Efficacy (lm/W)        | 74                  |

### Physical

|                          |            |
|--------------------------|------------|
| Colour                   | Black      |
| Orientation              | Adjustable |
| Rotation (°)             | 360        |
| Longitudinal tilting (°) | 90         |
| Net weight (kg)          | 0.25       |
| IP internal              | 20         |



\*installed in The Tracking Magnet

### Download

Mounting instructions [Download PDF](#)

### Photometric Files

LDT / IES [Download ZIP](#)


### Technical Drawings

2D [Download ZIP](#)

3D [Download ZIP](#)



Schematic light drawing



Photometric

|                          |                       |
|--------------------------|-----------------------|
| Lighting type            | Direct                |
| Light distribution       | Symmetric             |
| Rf fidelity index        | 92                    |
| Rg gamut index           | 100                   |
| LED Life / Failure Ratio | L80B50>47.000h_Tc85°C |
| Beam angle C0-180 (°)    | 15                    |
| Beam angle C90-270 (°)   | 15                    |
| Extreme cut off          | No                    |
| UGRL                     | <10                   |

Electrical

|                     |                 |
|---------------------|-----------------|
| Insulation class    | III             |
| Forward voltage (V) | 48              |
| LED current (mA)    | 250             |
| Power supply        | Remote excluded |
| Dimmable            | No              |
| Power supply type   | Non Dimmable    |
| Emergency           | No              |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Accessories & Power Supply



OPTIONAL  
Filter

08.0793.00

Honeycomb



OPTIONAL  
Filter

ACCESSORYTYPE4

08.0794.00

CCT Increaser Filter D58



OPTIONAL  
Filter

ACCESSORYTYPE4

08.0795.00

CCT Decreaser Filter