



05.9036.40A White

Light Shadow Spot 45 Dimmer On Board

Designed by FLOS Architectural, 2022



734lm - Beam° 21

LED accent lighting module for installation in The Tracking Magnet or Infra-Structure systems. For wireless control of luminaires, please select Casambi integrated versions. Accessories available, (honeycomb and CCT dichroic filters).

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
System power (W)	10
Source flux (lm)	909
System flux (lm)	734
Efficacy (lm/W)	74

Physical

Color	White
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Net weight (lb)	0.56
Gross weight (lb)	0.78
IP internal	20



*installed in The Tracking Magnet

Download

Family spec sheet	ZIP
Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
Rf fidelity index	92
Rg gamut index	100
LED Life / Failure Ratio	L80B50>47.000h_Tc85°C
Beam angle C0-180 (°)	21
Beam angle C90-270 (°)	21
Extreme cut off	No
UGRL	<10

Electrical

Insulation class	III
Forward voltage (V)	48
LED current (mA)	250
Driver	Remote excluded
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Accessories & Power Supply



OPTIONAL
Filter

08.0793.00

Honeycomb



OPTIONAL
Filter

ACCESSORYTYPE4

08.0794.00

CCT Increaser Filter D58



OPTIONAL
Filter

ACCESSORYTYPE4

08.0795.00

CCT Decreaser Filter