


## Light Shadow Spot 60 Casambi

Designed by FLOS Architectural, 2022

22W - 1431lm - 3000K - CRI> 90 - Beam° 33

Projector to be installed on threephase track with LED light source. Built-in 220-240V, 50-60Hz power supply. All finishes come with black track adapter, arm and back of the head. In the "all white" versions the track adapter, arm and back of the head come in white. The display is always offered in high loss technical black anti-glare finish. For other finishes, please consult us.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | LED array           |
| Power (W)              | 22                  |
| Source flux (lm)       | 1751                |
| Lumen Output (lm)      | 1431                |

### Physical

|                          |             |
|--------------------------|-------------|
| Colour                   | White/White |
| Orientation              | Adjustable  |
| Rotation (°)             | 360         |
| Longitudinal tilting (°) | 90          |
| Net weight (kg)          | 0.5         |
| IP internal              | 20          |

### Download


Mounting instructions [↓ PDF](#)

### Photometric Files


LDT / IES [↓ ZIP](#)

### Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Schematic light drawing



Photometric

|                          |                       |
|--------------------------|-----------------------|
| Lighting type            | Direct                |
| Light distribution       | Symmetric             |
| CCT (K)                  | 3000                  |
| CRI>                     | 90                    |
| Rf fidelity index        | 92                    |
| Rg gamut index           | 100                   |
| LED Life / Failure Ratio | L80B50>47.000h_Tc85°C |
| Beam angle C0-180 (°)    | 33                    |
| Beam angle C90-270 (°)   | 33                    |

Electrical

|                    |                  |
|--------------------|------------------|
| Insulation class   | II               |
| Frequency (Hz)     | 50/60            |
| Main voltage (Vac) | 220-240          |
| LED current (mA)   | 500              |
| Power supply       | Integrated       |
| Dimmable           | Yes              |
| Power supply type  | Dimmable Casambi |
| Dimming range (%)  | 1-100            |

Accessories & Power Supply



OPTIONAL  
Filter

ACCESSORYTYPE4

08.0796.00

CCT Increaser Filter D58 for LS  
Spot 60 SuperSpot



OPTIONAL  
Filter

ACCESSORYTYPE4

08.0797.00

CCT Decreaser Filter D12 for LS  
Spot 60 SuperSpot



OPTIONAL  
Filter

ACCESSORYTYPE4

08.0798.00

CCT Increaser Filter D58 for LS  
Spot 60 Spot / Medium / Flood /  
Wide Flood



OPTIONAL  
Filter

ACCESSORYTYPE4

08.0799.00

CCT Decreaser Filter D12 for LS  
Spot 60 Spot / Medium / Flood /  
Wide Flood



OPTIONAL  
Accessory

08.0175.14

Honeycomb for LS SPOT 60  
SuperSpot



OPTIONAL  
Accessory

08.0176.14

Honeycomb for LS SPOT 60 Spot  
/ Medium / Flood / Wide Flood