

Light Shadow Spot Broadcast

Designed by FLOS Architectural, 2026



LED - Power LED - 3W - 276lm - 4000K - CRI> 90 - Beam° 43

LED accent lighting module for installation in the The Micro Running Magnet Pro system. Integrated DC/DC electronic converter. Broadcast version, with simultaneous control of all luminaires.

 Drawing Thumbnail

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	3
Source flux (lm)	335
Lumen Output (lm)	276

Physical

Colour	White
Orientation	Adjustable
Rotation (°)	267
Longitudinal tilting (°)	90
Spot diameter (mm)	35
Length (mm)	41
Net weight (kg)	0.09
IP internal	20

Download

Mounting instructions

ZIP

Photometric Files

LDT / IES

ZIP

Technical Drawings

2D

ZIP

3D

ZIP


Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	90
Beam angle C0-180 (°)	43
Beam angle C90-270 (°)	43
Extreme cut off	No
UGR _L	<10

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	880
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Non Dimmable, Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No