


Light Shadow Surface 4 Spots Optic Medium

Designed by FLOS Architectural




LED - Power LED - 11W - 744lm - 2700K - CRI> 90 - Beam° 22

Surface luminaire with 4 LED lighting spots. For remote power source, not included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	11
Source flux (lm)	1080
System flux (lm)	744

Physical

Color	White/Black/White
Orientation	Fixed
Length (in)	7
Net weight (lb)	1.33
Gross weight (lb)	1.44
Package volume (in)	62
IP internal	44

Download


Family spec sheet [ZIP](#)
Mounting instructions [PDF](#)


Photometric Files

LDT / IES [ZIP](#)




Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional

 Replaceable control gear by a professional

Schematic light drawing




Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	22
Beam angle C90-270 (°)	22
UGR _L	<10

Electrical

Forward voltage (V)	12
LED current (mA)	900
Driver	Remote
Dimmable	Yes
Dimming type	Non Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)

Accessories & Power Supply



REQUIRED

Installation

JBOX.0001.40


Custom Junction Box Light
Shadow Surface, Black, New
construction



REQUIRED

08.0252.14.19


Surface Spacer



REQUIRED

08.0252.40.19

Surface Spacer




REQUIRED

Installation

JBOX.0001.14

Custom Junction Box Light
Shadow Surface, Black, New
construction




REQUIRED

Power supply

SP40W900MA-10V-A01

Splice Box 7"x3-5/8"x1-1/4",
900mA , 40W, 0-10V Dimmable,
120/277V




REQUIRED

Power supply

SP18W900MA-LUE-S01

Splice Box 18W, 1% dim, Lutron
Digital Ecosystem




REQUIRED

Power supply

SP18W900MA-PEQ-S01

Splice Box 18W, 0.1% dim, Lutron
Digital Eco system 0.1% dim, Soft
on- Fade to dark, 900mA 120V.
Size: 9" x 3.59" x 1.25"



REQUIRED

Power supply

SP18W900MA-LDE-S01

Splice Box 18W, Soft on- Fade to
dark, 900mA 120V.