

# FLOS



03.9820.14C9S Black/Black/White

## Light Shadow Surface 4 Spots Optic Medium

Designed by FLOS Architectural




LED - Power LED - 11W - 1020lm - 2700K - CRI> 90 - Beam° 23

Surface luminaire with 4 LED lighting spots. For remote power source, not included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling surface     |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 11                  |
| System power (W)       | 10.8                |
| Source flux (lm)       | 1192                |
| System flux (lm)       | 1020                |
| Efficacy (lm/W)        | 94                  |

### Physical

|                     |                   |
|---------------------|-------------------|
| Color               | Black/Black/White |
| Orientation         | Fixed             |
| Length (in)         | 8.07              |
| Net weight (lb)     | 1.33              |
| Gross weight (lb)   | 1.44              |
| Package volume (in) | 62                |
| IP internal         | 44                |

### Download

|                       |                       |
|-----------------------|-----------------------|
| Family spec sheet     | <a href="#">↓ ZIP</a> |
| Mounting instructions | <a href="#">↓ PDF</a> |

### Photometric Files


|           |                       |
|-----------|-----------------------|
| LDT / IES | <a href="#">↓ ZIP</a> |
|-----------|-----------------------|

### Technical Drawings

|    |                       |
|----|-----------------------|
| 2D | <a href="#">↓ ZIP</a> |
| 3D | <a href="#">↓ ZIP</a> |



Schematic light drawing



Ecodesign and Energy  
Labelling

Replaceable (LED only)  
light source by a  
professional

Replaceable control  
gear by a professional

Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 2700      |
| CRI>                   | 90        |
| Beam angle C0-180 (°)  | 23        |
| Beam angle C90-270 (°) | 22        |
| Extreme cut off        | No        |
| UGRL                   | <10       |

Electrical

|                     |                                          |
|---------------------|------------------------------------------|
| Forward voltage (V) | 12                                       |
| LED current (mA)    | 900                                      |
| Driver              | Remote                                   |
| Dimmable            | Yes                                      |
| Dimming type        | Non Dimmable                             |
| Dimming interface   | Remote Dimmable<br>(Dimmer Not Included) |

Accessories & Power Supply



REQUIRED

08.0252.14.19


Surface Spacer



REQUIRED

08.0252.40.19

Surface Spacer




REQUIRED

ACCESSORYTYPE2

JBOX.0001.14

Custom Junction Box Light  
Shadow Surface, Black, New  
construction




REQUIRED

ACCESSORYTYPE2

JBOX.0001.40

Custom Junction Box Light  
Shadow Surface, Black, New  
construction




REQUIRED

Power supply

SP40W900MA-10V-A01

Splice Box 7"x3-5/8"x1-1/4",  
900mA , 40W, 0-10V Dimmable,  
120/277V




REQUIRED

Power supply

SP18W900MA-LUE-S01

Splice Box 18W, 1% dim, Lutron  
Digital Ecosystem




REQUIRED

Power supply

SP18W900MA-LDE-S01

Splice Box 18W, Soft on- Fade to  
dark, 900mA 120V.



REQUIRED

Power supply

SP18W900MA-PEQ-S01

Splice Box 18W, 0.1% dim, Lutron  
Digital Eco system 0.1% dim, Soft  
on- Fade to dark, 900mA 120V.  
Size: 9" x 3.59" x 1.25'