

FLOS



05.2210.14CQF Bronze/Black/Black

Light Shadow Surface 4 Spots Optic Medium

Designed by FLOS Architectural




10.8W - 1080lm - 2700K - CRI> 90 - Beam° 22

Surface luminaire with 4 LED lighting spots. Power source incorporated.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Power (W)	10.8
Source flux (lm)	1192
System flux (lm)	1080

Physical

Color	Bronze/Black/Black
Orientation	Fixed
Net weight (lb)	1.77
Gross weight (lb)	1.44
IP internal	44

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	22
Beam angle C90-270 (°)	22

Electrical

Frequency (Hz)	50/60
Main voltage (Vac)	120
Forward voltage (V)	12
Driver	Integrated
Dimmable	Yes
Dimming type	Mains Cut Dimming
Dimming interface	Remote Dimmable (Dimmer Not Included)

Accessories & Power Supply



REQUIRED

08.0252.14.19

Surface Spacer



REQUIRED

08.0252.40.19

Surface Spacer