

# FLOS



05.2200.14CQF Bronze/Black/Black

## Light Shadow Surface 4 Spots Optic Spot

Designed by FLOS Architectural




10.8W - 1060lm - 2700K - CRI> 90 - Beam° 11

Surface luminaire with 4 LED lighting spots. Power source incorporated.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling surface     |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Power (W)              | 10.8                |
| Source flux (lm)       | 1192                |
| System flux (lm)       | 1060                |

### Physical

|                   |                    |
|-------------------|--------------------|
| Color             | Bronze/Black/Black |
| Orientation       | Fixed              |
| Net weight (lb)   | 1.77               |
| Gross weight (lb) | 1.44               |
| IP internal       | 44                 |

### Download

[Family spec sheet](#) [ZIP](#)

[Mounting instructions](#) [PDF](#)

### Photometric Files

[LDT / IES](#) [ZIP](#)


### Technical Drawings

[2D](#) [ZIP](#)

[3D](#) [ZIP](#)



Schematic light drawing



Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 2700      |
| CRI>                   | 90        |
| Beam angle C0-180 (°)  | 11        |
| Beam angle C90-270 (°) | 12        |

Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Frequency (Hz)      | 50/60                                 |
| Main voltage (Vac)  | 120                                   |
| Forward voltage (V) | 12                                    |
| Driver              | Integrated                            |
| Dimmable            | Yes                                   |
| Dimming type        | Mains Cut Dimming                     |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |

Accessories & Power Supply



REQUIRED

08.0252.14.19

Surface Spacer



REQUIRED

08.0252.40.19

Surface Spacer