

## Light Shadow Surface 4 Spots Optic Spot

Designed by FLOS Architectural



11W - 1111lm - 3000K - CRI> 90 - Beam° 11

Surface luminaire with 4 LED lighting spots. Power source incorporated.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling surface     |
| Environments           | Indoor dry location |
| Light sources included | yes                 |
| LED type               | Power LED           |
| Number of lamps        | 1                   |
| Power (W)              | 11                  |
| System power (W)       | 10.8                |
| Source flux (lm)       | 1272                |
| System flux (lm)       | 1111                |
| Efficacy (lm/W)        | 102                 |

### Physical

|                     |                     |
|---------------------|---------------------|
| Color               | Bronze/Black/Bronze |
| Orientation         | Fixed               |
| Net weight (lb)     | 1.33                |
| Gross weight (lb)   | 1.44                |
| Package volume (in) | 61.02               |
| IP internal         | 44                  |

### Download

Family spec sheet [ZIP](#)  
Mounting instructions [PDF](#)

### Photometric Files


LDT / IES [ZIP](#)

### Technical Drawings

2D [ZIP](#)  
3D [ZIP](#)



Schematic light drawing



Photometric

|                          |                             |
|--------------------------|-----------------------------|
| Lighting type            | Direct                      |
| Light distribution       | Symmetric                   |
| CCT (K)                  | 3000                        |
| CRI>                     | 90                          |
| LED Life / Failure Ratio | L80B50>50.000h<br>(Tc=85°C) |
| Beam angle C0-180 (°)    | 11                          |
| Beam angle C90-270 (°)   | 11                          |
| Extreme cut off          | No                          |
| UGRL                     | <10                         |

Electrical

|                     |        |
|---------------------|--------|
| Insulation class    | III    |
| Forward voltage (V) | 12.9   |
| LED current (mA)    | 900    |
| Driver              | Remote |


Accessories & Power Supply




REQUIRED  
08.0252.14.19  
Surface Spacer




REQUIRED  
08.0252.40.19  
Surface Spacer




REQUIRED  
Power supply  
SP40W900MA-10V-A01  
Splice Box 7"x3-5/8"x1-1/4",  
900mA , 40W, 0-10V Dimmable,  
120/277V



REQUIRED  
Power supply  
SP18W900MA-LUE-S01  
Splice Box 18W, 1% dim, Lutron  
Digital Ecosystem



REQUIRED  
Power supply  
SP18W900MA-LDE-S01  
Splice Box 18W, Soft on- Fade to  
dark, 900mA 120V.



REQUIRED  
Power supply  
SP18W900MA-PEQ-S01  
Splice Box 18W, 0.1% dim, Lutron  
Digital Eco system 0.1% dim, Soft  
on- Fade to dark, 900mA 120V.  
Size: 9" x 3.59" x 1.25"