

Light Shadow Surface 4 Spots Optic Spot

Designed by FLOS Architectural



11W - 1011lm - 2700K - CRI> 90 - Beam° 11

Surface luminaire with 4 LED lighting spots. Power source incorporated.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light sources included	yes
LED type	Power LED
Number of lamps	1
Power (W)	11
System power (W)	10.8
Source flux (lm)	1192
System flux (lm)	1011
Efficacy (lm/W)	93

Physical

Color	Steel/Black/Black
Orientation	Fixed
Net weight (lb)	1.33
Gross weight (lb)	1.44
Package volume (in)	61.02
IP internal	44

Download

Family spec sheet [↓ ZIP](#)
Mounting instructions [↓ PDF](#)

Photometric Files


LDT / IES [↓ ZIP](#)

Technical Drawings

2D [↓ ZIP](#)
3D [↓ ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C)
Beam angle C0-180 (°)	11
Beam angle C90-270 (°)	12
Extreme cut off	No
UGRL	<10

Electrical

Insulation class	III
Forward voltage (V)	12.9
LED current (mA)	900
Driver	Remote


Accessories & Power Supply




REQUIRED
08.0252.14.19
Surface Spacer




REQUIRED
08.0252.40.19
Surface Spacer




REQUIRED
Power supply
SP40W900MA-10V-A01
Splice Box 7"x3-5/8"x1-1/4",
900mA , 40W, 0-10V Dimmable,
120/277V



REQUIRED
Power supply
SP18W900MA-LUE-S01
Splice Box 18W, 1% dim, Lutron
Digital Ecosystem



REQUIRED
Power supply
SP18W900MA-LDE-S01
Splice Box 18W, Soft on- Fade to
dark, 900mA 120V.



REQUIRED
Power supply
SP18W900MA-PEQ-S01
Splice Box 18W, 0.1% dim, Lutron
Digital Eco system 0.1% dim, Soft
on- Fade to dark, 900mA 120V.
Size: 9" x 3.59" x 1.25"