

Light Shadow Surface 4 Spots Optic Spot

Designed by FLOS Architectural




11W - 1079lm - 3000K - CRI> 90 - Beam° 11

Surface luminaire with 4 LED lighting spots. Power source incorporated.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light sources included	yes
LED type	Power LED
Number of lamps	1
Power (W)	11
System power (W)	10.8
Source flux (lm)	1272
System flux (lm)	1079
Efficacy (lm/W)	99

Physical

Color	Steel/Black/Black
Orientation	Fixed
Net weight (lb)	1.33
Gross weight (lb)	1.44
Package volume (in)	61.02
IP internal	44

Download

Family spec sheet [↓ ZIP](#)
Mounting instructions [↓ PDF](#)

Photometric Files


LDT / IES [↓ ZIP](#)

Technical Drawings

2D [↓ ZIP](#)
3D [↓ ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C)
Beam angle C0-180 (°)	11
Beam angle C90-270 (°)	12
Extreme cut off	No
UGRL	<10

Electrical

Insulation class	III
Forward voltage (V)	12.9
LED current (mA)	900
Driver	Remote


Accessories & Power Supply



REQUIRED

08.0252.14.19


Surface Spacer



REQUIRED

08.0252.40.19

Surface Spacer




REQUIRED

Power supply

SP40W900MA-10V-A01

Splice Box 7"x3-5/8"x1-1/4",
900mA , 40W, 0-10V Dimmable,
120/277V




REQUIRED

Power supply

SP18W900MA-LUE-S01

Splice Box 18W, 1% dim, Lutron
Digital Ecosystem




REQUIRED

Power supply

SP18W900MA-LDE-S01

Splice Box 18W, Soft on- Fade to
dark, 900mA 120V.



REQUIRED

Power supply

SP18W900MA-PEQ-S01

Splice Box 18W, 0.1% dim, Lutron
Digital Eco system 0.1% dim, Soft
on- Fade to dark, 900mA 120V.
Size: 9" x 3.59" x 1.25"