


## Light Shadow Surface 4 Spots Optic Wide Flood

Designed by FLOS Architectural



10.8W - 1022lm - 2700K - CRI> 90 - Beam° 45

Surface luminaire with 4 LED lighting spots. Power source incorporated.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling surface     |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Power (W)              | 10.8                |
| Source flux (lm)       | 1192                |
| System flux (lm)       | 1022                |

### Physical

|                   |                   |
|-------------------|-------------------|
| Color             | White/Black/White |
| Orientation       | Fixed             |
| Net weight (lb)   | 1.33              |
| Gross weight (lb) | 1.44              |
| IP internal       | 44                |

### Download

|                       |                       |
|-----------------------|-----------------------|
| Family spec sheet     | <a href="#">↓ ZIP</a> |
| Mounting instructions | <a href="#">↓ PDF</a> |

### Photometric Files


|           |                       |
|-----------|-----------------------|
| LDT / IES | <a href="#">↓ ZIP</a> |
|-----------|-----------------------|

### Technical Drawings

|    |                       |
|----|-----------------------|
| 2D | <a href="#">↓ ZIP</a> |
| 3D | <a href="#">↓ ZIP</a> |



Schematic light drawing



Ecodesign and Energy  
Labelling

Replaceable (LED only)  
light source by a  
professional

Replaceable control  
gear by a professional

Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 2700      |
| CRI>                   | 90        |
| Beam angle C0-180 (°)  | 45        |
| Beam angle C90-270 (°) | 44        |

Electrical

|                     |                                          |
|---------------------|------------------------------------------|
| Frequency (Hz)      | 50/60                                    |
| Main voltage (Vac)  | 120                                      |
| Forward voltage (V) | 12                                       |
| LED current (mA)    | 900                                      |
| Driver              | Integrated                               |
| Dimmable            | Yes                                      |
| Dimming type        | Mains Cut Dimming                        |
| Dimming interface   | Remote Dimmable<br>(Dimmer Not Included) |

Accessories & Power Supply



REQUIRED

08.0252.14.19

Surface Spacer



REQUIRED

08.0252.40.19

Surface Spacer