

Light Shadow Surface 4 Spots Optic Wide Flood

Designed by FLOS Architectural



10.8W - 1048lm - 3000K - CRI> 90 - Beam° 44

Surface luminaire with 4 LED lighting spots. Power source 120-227V incorporated.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Power (W)	10.8
Source flux (lm)	1272
System flux (lm)	1048

Physical

Color	White/White/Black
Trim	No
Orientation	Fixed
Net weight (lb)	1.33
Gross weight (lb)	1.44
IP internal	44

Download

Family spec sheet [ZIP](#)
Mounting instructions [PDF](#)

Photometric Files


LDT / IES [ZIP](#)

Technical Drawings

2D [ZIP](#)
3D [ZIP](#)



Schematic light drawing



Ecodesign and Energy
Labelling

Replaceable (LED only)
light source by a
professional

Replaceable control
gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	44
Beam angle C90-270 (°)	43

Electrical

Frequency (Hz)	50/60
Main voltage (Vac)	120-277
Forward voltage (V)	12
LED current (mA)	900
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 0-10V
Dimming interface	Remote Dimmable (Dimmer Not Included)

Accessories & Power Supply



REQUIRED

08.0252.14.19

Surface Spacer



REQUIRED

08.0252.40.19

Surface Spacer