

## Light Shadow Surface 4 Spots Optic Wide Flood

Designed by FLOS Architectural



LED - Power LED - 10.8W - 982lm - 2700K - CRI> 90 - Beam° 44

Surface luminaire with 4 LED lighting spots. Power source 220-240V incorporated.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling surface     |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 10.8                |
| System power (W)       | 10.8                |
| Source flux (lm)       | 1192                |
| Lumen Output (lm)      | 982                 |
| Efficacy (lm/W)        | 90                  |

### Physical

|                 |                   |
|-----------------|-------------------|
| Colour          | Black/Black/Black |
| Trim            | No                |
| Orientation     | Fixed             |
| Length (mm)     | 146               |
| Net weight (kg) | 0.8               |
| IP internal     | 44                |

### Download

Mounting instructions  PDF

### Photometric Files

LDT / IES  ZIP


### Technical Drawings

2D  ZIP

3D  ZIP



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 2700      |
| CRI>                   | 90        |
| Beam angle C0-180 (°)  | 44        |
| Beam angle C90-270 (°) | 43        |
| Extreme cut off        | No        |
| UGRL                   | <10       |

Electrical

|                    |              |
|--------------------|--------------|
| Insulation class   | I            |
| Frequency (Hz)     | 50/60        |
| Main voltage (Vac) | 220-240      |
| Power supply       | Integrated   |
| Dimmable           | No           |
| Power supply type  | Non Dimmable |
| Emergency          | No           |