

FLOS



03.9861.40C9S Black/White/Black

Light Shadow Surface 4 Spots Optic Wide Flood

Designed by FLOS Architectural




LED - Power LED - 11W - 982lm - 2700K - CRI> 90 - Beam° 44

Surface luminaire with 4 LED lighting spots. For remote power source, not included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	11
System power (W)	10.8
Source flux (lm)	1192
System flux (lm)	982
Efficacy (lm/W)	90

Physical

Color	Black/White/Black
Orientation	Fixed
Net weight (lb)	1.33
Gross weight (lb)	1.44
Package volume (in)	62
IP internal	44

Download

Family spec sheet	↓ ZIP
Mounting instructions	↓ PDF

Photometric Files


LDT / IES	↓ ZIP
-----------	-------

Technical Drawings

2D	↓ ZIP
3D	↓ ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	44
Beam angle C90-270 (°)	43
Extreme cut off	No
UGRL	<10

Electrical

Forward voltage (V)	12
LED current (mA)	900
Driver	Remote
Dimmable	Yes
Dimming type	Non Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)

Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Accessories & Power Supply



REQUIRED

08.0252.14.19


Surface Spacer



REQUIRED

08.0252.40.19

Surface Spacer




REQUIRED

ACCESSORYTYPE2

JBOX.0001.14

Custom Junction Box Light
Shadow Surface, Black, New
construction




REQUIRED

ACCESSORYTYPE2

JBOX.0001.40

Custom Junction Box Light
Shadow Surface, Black, New
construction




REQUIRED

Power supply

SP40W900MA-10V-A01

Splice Box 7"x3-5/8"x1-1/4",
900mA , 40W, 0-10V Dimmable,
120/277V




REQUIRED

Power supply

SP18W900MA-LUE-S01

Splice Box 18W, 1% dim, Lutron
Digital Ecosystem




REQUIRED

Power supply

SP18W900MA-LDE-S01

Splice Box 18W, Soft on- Fade to
dark, 900mA 120V.



REQUIRED

Power supply

SP18W900MA-PEQ-S01

Splice Box 18W, 0.1% dim, Lutron
Digital Eco system 0.1% dim, Soft
on- Fade to dark, 900mA 120V.
Size: 9" x 3.59" x 1.25'